



NOTES:

1. PRECAST COMPONENTS MANUFACTURED AND SUPPLIED TO MEET OR EXCEED ASTM C76/AASHTO M170, OTHER APPLICABLE ASTM SPECIFICATIONS, AND EACH CORRESPONDING AASHTO SPECIFICATION.
2. JOINTS MANUFACTURED AND SUPPLIED (WITH GASKETS) TO MEET OR EXCEED ASTM C1628 AND C443/AASHTO M198.
3. REINFORCEMENT NOT SHOWN FOR CLARITY.
4. NOMINAL MEASUREMENTS ARE SHOWN. ACTUAL VALUES MAY BE SLIGHTLY ADJUSTED TO SUIT PRECAST FORMS.

ØEQUIV	SPAN	RISE	WT	A	B	C	D	E
18"	23"	14"	3 ⁵ / ₈ "	73"	46"	27"	32"	6"
24"	30"	19"	3 ¹ / ₄ "	73"	38"	35"	42"	9"
30"	38"	24"	3 ³ / ₄ "	74"	30"	44"	48"	10"
36"	45"	29"	4 ¹ / ₂ "	98"	39"	59"	66"	13"



SCALE: 1:32 DATE: 04/14/09 DWG: 5010-01

FLARED END SECTION
23"x14"-45"x29"
SINGLE OFFSET JOINT